



DO NOT FULLY TIGHTEN THE BOLTS BEFORE ASSEMBLING ALL THE PARTS

Assembly is easier with two people, one to hold the parts and a second person to insert the fixings.

1. Lay out and identify all the components. Do not tighten any fixings until the assembly is complete. Please refer to diagram for positioning.

2. Assemble the Legs (E) to the bottom of Base Panel (D) using four M6 x 15 Bolts (T2) and Nuts (V). It might be easier to do this on a table with the components upside down.

(Note: Do not assemble the legs to the side edge of the base panel yet)

3. Assemble the bottom of the Side Panel (C) through the Base Panel (D) to the Legs (E) by placing two Side Panels (C) inside the Base Panel (D) and fix to the Leg (E) with inserting one M6 x 25 Bolts (T1) through the Leg (E), Base Panel (D) to the hole with the adjacent edge of the two Side Panels (C) together and fix with Nuts (V).

Repeat the procedure to fix the other Side Panels (C) to the Legs (E) through Base Panel (D).

(Note: The bottom hole with adjacent edge in-between two side panels fix at the same time through the base panel to the legs).

4. Now assemble the top of Four Side Panels (C) together with four M6 x 15 Bolts (T2) and Nuts (V)

5. Place the assembled components so that four feet are on the ground and the assembled brazier is vertical.

6. Straighten the legs, so that the brazier is properly upright and then using a power driver if available and spanner, tighten all nuts and bolts.

7. Place the BBQ Grill (B) and Hooks (A) on top of assembled brazier.

Now check and tighten all fixings, assembly is complete.

DO NOT OVER TIGHTEN THE FIXINGS