



1300w Electric 33cm Lawnmower

WEER33
1938122002

en - Original Instructions

Sales & Support: 01793 333212

Before use please read & understand this manual; paying particular attention to the safety instructions.
The manufacturer reserves the right to change the product specification and livery according to continues product improvements.




Instruction Manual

CONTENTS

SPECIFICATION
COMPONENTS
SAFETY INSTRUCTIONS
ASSEMBLY
OPERATION
MAINTENANCE
STORAGE
TROUBLE SHOOTING
PARTS DIAGRAM & LIST
WARRANTY
DECLARATION OF CONFORMITY

SPECIFICATION

Model	WEER33
Product No.	1938122002
Motor – Rated Power	1300W
Motor – Rated Voltage	230-240V ~50Hz
No Load Speed	3600rpm
Cutting Width	33cm
Height of Cut	25-65mm
Height Adjustments	5
Grassbox Capacity	35L
Sound Pressure Level	84dB(A)
Guaranteed Sound Power Level	89dB(A)
Vibration	3.47m/s ²
Insulation	 Double Insulated IPX4
Weight	N.W 8.8kg – G.W 10.5kg

COMPONENTS



1	Handle	7	Switch Box
2	Trigger	8	Grassbox Full Indicator
3	Safety Button	9	Grassbox
4	Electric Cable	10	Rear Wheel
5	Electric Cable Clips	11	Front Wheel
6	Single Height Adjuster		

Carefully remove the machine from its packaging and check that you have all the components.

If parts are missing or damaged, please contact us:

Telephone: 01793 333212
(Mon to Fri 8.00am to 5.30pm excl. Bank Holidays)

Email: customerservice@webbgardenpower.co.uk



Instruction Manual

SAFETY INSTRUCTIONS - SAVE THESE INSTRUCTIONS FOR FUTURE USE



WARNING

Read this instruction manual carefully before operating this lawn mower. Make sure that you are familiar with the controls and properly operate the machine. Following these instructions can reduce the risk of fire, electric shock and personal injury.

IF NOT USED PROPERLY THIS LAWN MOWER CAN BE DANGEROUS!

This lawn mower can cause serious injury to the operator and others, the warning and safety instructions must be followed to ensure reasonable safety and efficiency in using this lawn mower. The operator is responsible for following the warning and safety instructions in this manual and on the lawn mower. Never use the lawn mower unless the grass box or guards are correctly positioned.

THE LAWN MOWER IS DESIGNED FOR DOMESTIC USE ONLY.

Lawn mowers for use in private gardens are mowers whose annual use does not generally exceed 50 hours and that are primarily used for tending GRASS OR LAWN AREAS, but not in public facilities, parks or sports grounds and not for agricultural or forestry use.

Compliance with the operating manual supplied by the manufacturer is a prerequisite for the proper usage of the lawn mower. The operating manual contains servicing and maintenance instructions as well as directions for use.

IMPORTANT

The lawn mower must not be used to trim bushes, hedges and shrubs, to cut or shred climbing plants or lawns on roof gardens or in balcony boxes or to clean footpaths, nor must it be used as a chopper for shredding tree or hedge cuttings.

Furthermore, the lawn mower must not be used as a cultivator or to level off uneven areas of ground, e.g. molehills.

TRAINING
















Read the instructions carefully: Be familiar with the controls and the proper use of the equipment.

Never allow children or people unfamiliar with these instructions to use the lawnmower. Local regulations can restrict the age of the operator.

Never operate the mower while people, especially children, or pets are nearby.

Keep in mind that the operator or user is responsible for accidents or hazards involving the lawnmower that occur to other people or their property.

SYMBOLS

	Read the instruction handbook before operating this machine.		Beware of flying objects. Keep all bystanders, especially children & pets, at least 15m away from the operating area.
	Class II, double insulation		Do not expose to rain or damp condition
	Keep hands and feet clear of the cutting deck when the machine is running.		The cutting blade will continue to rotate after the motor is switched off
	Keep the supply flexible cord away from the cutting blades		Remove all objects that could be thrown by the blade in the working area.
	Wear Ear & Eye Protection		Before working or undertaking any servicing or cleaning of the machine, ensure the electrical cable is removed from the power source.
	Be careful when using on slopes. Do not operate on inclines greater than 15°. It is advised to cut across the incline.		Safety alert symbol. Used to alert you to potential personal injury hazards. Obey all safety messages that follow this symbol to avoid possible injury.
 DANGER	Indicates an imminently hazardous situation which, if not avoided, will result in serious injury.	 WARNING	Indicates a potentially hazardous situation which, if not avoided, could result in serious injury.
 CAUTION	Indicates a potentially hazardous situation which, if not avoided, may result in minor or moderate injury.	CAUTION	Used without the safety alert symbol, indicates a potentially hazardous situation which, if not avoided, may result in property damage.

Correct Disposal of this product




This marking indicates that this product should not be disposed with other household wastes throughout the EU. To prevent possible harm to the environment or human health from uncontrolled waste disposal, recycle it responsibly to promote the sustainable reuse of material resources. To return your used device, please use the return and collection systems or contact the retailer where the product was purchased. They can take this product for environmental safe recycling.



Instruction Manual

PREPARATION

- Always wear appropriate footwear, such as work boots, and trousers when operating the mower. Do not operate the equipment when barefoot or wearing open sandals. Always wear safety goggles or safety glasses with side shields when operating the mower.



- Thoroughly inspect the area where the equipment is to be used and remove all objects which can be thrown by the machine.
- Before using, always visually inspect to see that the blades, blade bolts and cutter assembly are not worn or damaged. Replace worn or damaged blades and bolts in sets to preserve balance.
- Only use accessories approved by the manufacturer.
- Do not operate the machine while under the influence of alcohol or drugs.
- Never operate the machine in wet grass. This could cause you to slip while mowing.

ELECTRICAL SAFETY

- Power plugs must match the outlet. Never modify the plug in any way. Do not use any adapter plugs with earthed (grounded) power tools. Unmodified plugs and matching outlets will reduce risk of electric shock.
- Avoid unintentional starting. Always check that the switch is in Off position before plugging in the product to the power supply. Do not carry a plugged in product with your finger on the switch.
- Avoid body contact with earthed or grounded surfaces, such as pipes, radiators, ranges and refrigerators. There is an increased risk of electric shock if your body is earthed or grounded.
- Do not expose the product to rain or wet conditions.
- Water entering an appliance will increase the risk of electric shock.
- Electrical power should be supplied via a residual current device (RCD) with a tripping current of not more than 30 mA.
- Before use, check the supply and extension cord for signs of damage or aging. If the cord becomes damaged during use, disconnect the cord from the supply immediately. **Do not touch the cord before disconnecting the supply.** Do not use the product if the cord is damaged or worn.
- If you need to use an extension cable, ensure it is suitable for outdoor use and has a current capacity rating, sufficient to supply your product. Check it before every use for damage, always uncoil it completely, during use because coiled cables can overheat. Damaged extension cables should not be repaired; they should be replaced with an equivalent type.

- Make sure the power cable is positioned so that it cannot be damaged by the cutting means and will not be stepped on, tripped over or otherwise subjected to damage or stress.
- Never pick up or carry the product by the electric cable.
- Never pull by the power cord to disconnect from the power supply.
- Keep the power cord away from heat, oil and sharp edges.
- Make sure voltage is correct for your product. A nameplate on the product indicates the product's voltage. Never connect the product to an AC voltage that differs from this voltage.
- Always ensure the cord from the handlebar to the mower body is never trapped, pinched or otherwise damaged during assembly or handle folding. Never apply power to the mower if this cable is damaged. Return to authorised service centre for professional repair.

OPERATION

- Only operate the mower in daylight or in good artificial light.
- Avoid operating the equipment in wet grass.
- Always be sure of your footing on slopes. Exercise extreme caution when changing direction on slopes. Do not mow excessively steep slopes, which exceed 15°. For wheeled rotary machines, mow across the face of slopes, never up and down.
- Never run while using the mower, always walk.
- Do not pull the mower backwards unless absolutely necessary. Use extreme caution when reversing or pulling the lawnmower towards you.
- Stop the blade(s) if the lawnmower has to be tilted for transportation when crossing surfaces other than grass (such as gravel drives, walks, or roads) & when transporting the lawnmower to & from the area to be mowed. Never pick up or carry a lawnmower while the electric motor is running.
- Never operate the lawnmower with defective guards, or without safety devices, for example deflectors and/or grass catchers, in place.
- Do not put hands or feet near or under rotating parts. Keep clear of the discharge opening at all times.

Stop the motor and disconnect the electrical plug from the power source:

- ✓ before clearing blockages or unclogging the chute;
- ✓ before checking, cleaning or working on the lawnmower;
- ✓ after striking a foreign object inspect the lawnmower for damage and make repairs before restarting and operating the lawnmower,
- ✓ if lawnmower starts to vibrate abnormally (check immediately).
- Shut the motor off and wait until the motor and the blade come to a complete stop before removing the grass catcher.
- Watch for holes, ruts, or bumps. Tall grass can hide obstacles.
- Do not mow near drop-offs, ditches or embankments. The operator could lose footing or balance.
- Be alert and turn the machine off if children enter the area.
- Never tamper with safety devices. Check their proper operation regularly.
- Never attempt to make wheel height adjustments while the motor is running.



Instruction Manual

GENERAL MOWING TIPS

- When cutting long grass, reduce walking speed to allow for more effective cutting and a proper discharge of the clippings. It is recommended that you cut longer grass in stages. Start at a higher cutting height and go over the same area a second time with a lower cutting height.
- Do not cut wet grass; it will stick to the underside of the deck and prevent proper collection or discharge of grass clippings.
- New or thick grass may require a higher cutting height.
- Empty the grass box regularly, the discharge chute will become blocked with grass cuttings.
- The mower is designed to operate and cut most effectively when moving forwards.

OVERLOAD PROTECTION

- The product has an overload protection device. When overloading is detected, the product will automatically switch off. If the overload protector is actuated, the motor must be allowed to cool down for 5 to 10 minutes.
- Turn off the power and remove the plug from the supply. The blades are sharp, wear heavy duty gloves before touching. Make sure the blade can rotate freely and is not jammed or tight.
- When the motor is cool, connect the plug to the power supply, turn the power on. Press the Safety Button & then the Trigger to start the product. If the product will still not start, return it to an authorised service centre for repair.

MAINTENANCE AND STORAGE

- Keep all nuts, bolts and screws tight to be sure the equipment is in safe working condition.
- Replace worn or damaged parts for safety.
- Keep the machine free of grass, leaves, or other debris build-up.
- Allow the machine to cool before storing.
- Grass catcher components are subject to wear, damage, & deterioration, which could expose moving parts or allow objects to be thrown. Frequently check & replace them with the manufacturer's recommended parts, when necessary.
- Mower blades are sharp and can be dangerous. Wrap the blade(s) or wear gloves, and use extra caution when servicing them.

ASSEMBLY

ASSEMBLY/PRE-OPERATION


Read these instructions in its entirety before you attempt to assemble and operate your new lawnmower.

REMOVE LAWN MOWER FROM CARTON

Roll the lawn mower out of the carton and check thoroughly for additional loose parts. Please ensure that you have all the below necessary parts, before commencing with the assembly. In the unlikely event that you are missing a component, please do contact us on **01793 333212, option 2** or email **customerservice@handydistribution.co.uk** for assistance.



x1



x2

x1



x2



x2



x2






Instruction Manual


HANDLE ASSEMBLY

- Insert the lower handles into the deck of the machine, individually. Press the height adjustment button to allow the lower handle to be inserted and ensure both handles are fixed to the same height.
- Slide the Cable Restraint over the left hand side of the Upper Handle and secure the Upper Handle to the Lower Handles using the Handle Knob and Bolts provided.
- Ensure the Electric Cable run down the outside of the handle assembly.
- Secure the Electric Cable to the handle assembly, using the Cable Clips provided.



GRASSBOX COLLECTOR

- Ensure the lower mesh collector is fully clear open and away from the collector top.
- Lift the Grass Flap.
- Secure The Grassbox to the machine, ensuring the hooks are firmly housed onto the machine deck.




OPERATION

STARTING THE MACHINE

Ensure the machine is within the working grassed area.

Plug the machine into the electric supply, ensuring it meets the recommended requirements.

Feed the cable through the cable restraint as imaged



Press the Safety Button (A) and pull the Trigger (B) towards the main handle.



The mower will start and blade immediately rotate.

When operating the machine, you can release the Safety Button and the machine will still operate.

STOP THE MOTOR

To stop the motor, release the Trigger. (WARNING – The blade will still rotate for a small time, after the trigger has been released).






Instruction Manual

ADJUST THE CUTTING HEIGHT

Raise the wheels for a low cut and lower the wheels for a high cut, adjust the cutting height to suit your requirements. Medium position is best for most lawns.

The single height adjustment lever is located on the front axle, left wheel.




Push the lever towards the wheel and rotate up or down the five settings, depending on your needs.



GRASSBOX FULL INDICATOR

Your machine grassbox collector is fitted with a full indicator at the rear of the hard top. Whilst air is still rotating around the collector and grass is being collected, the flap will raise and remain open.



Once the collector is full, the flap will remain closed and you should empty the grassbox.



MOWING TIPS

Under certain conditions, such as very tall grass, it may be necessary to raise the height of cut to reduce pushing effort, prevent overloading of the motor and leaving clumps of grass clippings.

It may also be necessary to reduce ground speed and/or push the lawn mower over the area a second time. For extremely heavy cutting, reduce the width of cut by overlapping the previously cut path and mow slowly. The side combs allow the machine to cut up to walls.



When cutting on slopes, ensure your footing is secure, the grass is not wet and the machine is used across the slope and not up or down the slope. The slope gradient should not exceed 15°.



Instruction Manual

MAINTENANCE

IMPORTANT - Regular, careful maintenance is essential for keeping the safety level and original performance of the machine unchanged over time.


1. Keep all nuts, bolts and screws tight to be sure the equipment is in safe working condition.
Regular maintenance is essential for safety and performance.
2. Do not use the equipment with worn or damaged parts, this can be dangerous. Parts are to be replaced and not repaired. Use genuine spare parts. Parts that are not of the same quality can damage the equipment and create safety hazards.
3. Wear strong work gloves when removing and reassembling the blade.
4. Check the blade's balance after sharpening.
5. Check the grass flap and grassbox collector frequently for wear and deterioration.
6. Whenever the machine is to be handled, transported or tilted you must:
 - ✓ Wear strong working gloves;
 - ✓ Grasp the machine at the points that offer a safe grip, taking account of the blades, the mower's weight and its distribution.

BLADE MAINTENANCE



The cutting blade will continue to rotate after the motor is switched off. Slicing is possible if care is not taken. Wear appropriate hand coverage.

Remove the electric plug from the mains supply. Clean the underside of the deck with a stiff brush, before any maintenance is undertaken to the blade.







REMOVE AND REPLACE THE BLADE.

Block the rotation of the blade, using a good sized piece of wood, which the blade cannot cut. Hold the blade using gardening gloves (not provided) and spanner wrench (not provided) rotating the spanner anti-clockwise.

Remove the bolt, washer and blade. Dispose of the old blade responsibly.

Attach a new blade, fastening with the washer and blade bolt. Ensure that the blade is correctly positioned on the blade boss and then firmly tighten the bolt, clockwise.





CLEANING

Always remove the electric plug from the mains supply, before any cleaning is undertaken.



Carefully clean the underside of the deck with a stiff brush after each cut; remove the grass debris and mud accumulated inside the deck to prevent it drying. Remove the belt casing by removing the screws and clean around the transmission and drive belts with a brush or compressed air once or twice a year. **Do not use water on any part of the main machine!**





Instruction Manual

GRASSBOX COLLECTOR CLEANING

Pores in the grassbox can become filled with dirt and dust, during use and will collect less grass. To prevent this, regularly hose the catcher off with water and let dry before using.

Keep the top of the motor housing vents clear and clean of grass clippings & dust. This will assist motor air flow and extend the machine life.

STORAGE

For trouble free service, make sure the machine is clean and dry before storing.

Please ensure the machine is stored away from direct sunlight.





Store indoors or in a safe, locked protected area during severe weather and winter months.

If storing for an extended period, inspect, clean and repair the machine if necessary.

Store in a clean, dry, dust free area.

Ensure the machine is stored in a position, where any persons cannot step on to attempt to reach items up high, due to risk of movement.

For compact storage, follow the below steps.



TROUBLE SHOOTING

ISSUE	CORRECTION
Motor does not run	<ol style="list-style-type: none">1. Check the mains connection cable, plug fuse and circuit breaker.2. Start on short grass or on an area which has already been mown.3. Unplug the mower. Clean the discharge chute/housing, the blade must rotate freely.4. Correct the cutting height.
Reduced Motor Power	<ol style="list-style-type: none">1. Correct the cutting height.2. Clean the discharge chute/housing.3. Have the blade re-sharpened or replaced by an authorised service dealer.
The grass collector does not fill completely	<ol style="list-style-type: none">1. Correct the cutting height.2. Allow the lawn to dry.3. Have the blade re-sharpened or replaced by an authorised service dealer.4. Clean the grille on the grass catcher.5. Clean the discharge chute/housing.

Notes

Notes



EC DECLARATION OF CONFORMITY

We Handy Distribution Ltd - SN3 5HY (Importer) declare that the product:

Designation: 33cm 1300W Electric Rotary Lawnmower

Model(s): WEER33

Product Number: 1938122002

Type/Serial No. As per rating label on machine

Complies with the following directives:

Machinery Directive 2006/42/EC

Electromagnetic Capability Directive 2014/30/EU

Noise Emission Directive 2000/14/EC amended by 2005/88/EC

The conformity assessment procedure followed was in accordance with

EN60335-1 :2012+A11:2014, EN60335-2-77:2010, EN62233 :2008

EN55014-1 :2006/+A1 :2009/+A2/2011, EN55014-2 :2015, EN61000-3-2 :2014, EN61000-3-11 :2000

ISO 11094 :1991, EN ISO 3744 :1995 & Annex III of 2000/14/EC amended by 2005/88/EC

Measured Sound Pressure Level: $L_{PA} = 84\text{dB(A)}$

Measured Sound Power Level: $L_{WA} = 89\text{dB(A)}$

Vibration Level: 3.47 m/s^2

Notified Body:

Intertek Testing Services Shanghai

Addresses:

Building No. 86, 1198 Qinzhou Road (North), Caohejing Development Zone, Shanghai 200233, P.R.C

Authorised signatory and technical file holder

Date: 13/09/2017

Signature:

Name: Mr Simon Belcher

Position: Managing Director

Company: Handy Distribution Ltd

Address: Murdock Rd, Swindon, Wiltshire, SN3 5HY.



Notes



Instruction Manual

This Service Book is provided with your Webb, to help you look after your purchase to our recommendations and enable you to take advantage of the conditional manufacturer domestic warranty*.


Present this service book to your authorised Webb repair dealer, whenever a service or a warranty appraisal is required.

The booklet is applicable to the following products, in the UK only:

Ride On Lawn Tractors
Cylinder Lawnmowers
Petrol Rotary Lawnmowers
Petrol Hand Held Range

Please register your machine using the following pages or at www.webbgardenpower.co.uk. By registering your machine, you agree to maintain the machine in accordance with the service schedules specified in this manual and services duly recorded. (Not applicable for Webb electric handheld machines). You may be asked to produce this booklet as proof of servicing in the event of a claim. Proof of purchase should also be kept as a reference.

Ensure you have the following information available from your machine product label. The two examples below can be found on your machine:



1. Model Number

2. Serial & Product Number

Please complete using BLOCK CAPITALS.
Sections marked* must be completed to validate Warranty.

1. Users Statement of Warranty

Each new machine is warranted against defective material or assembly of material under normal usage. The warranty applies to the original purchaser, is not transferable and covers faulty parts and the labour involved in replacing and repairing those parts, which are of original manufacture.

2. Period of Warranty

Webb (excludes Electric Handheld) & Webb Pro, 2 year conditional warranty from the original date of sale to the first domestic user.

Webb Electric Handheld & Dynamic 1 year warranty from the original date of sale to the first domestic user.

90 days from the original date of sale to the professional/commercial or for hire user.

Engine warranty as per the engine manufacturer's warranty, which will be supplied with the machine.

90 days from the original date of sale for Replacement Spare Parts

All machines' must be serviced within the first 14 months from the original date of purchase, to qualify for a second year parts & labour warranty, details of the service must be recorded in the service record within this manual.

A reduced warranty period of 90 days applies to those items which are subject to normal wear and tear and in normal use, will need replacement or adjustment.

These items are chargeable after 90 days of ownership.

Filters
Tyres / Wheels
Drive chains and belts
Brake & clutch friction components
Control cable & starter cords
Fluids & lubricants
Spark plugs
Blades (Lawnmowers & Brushcutters)
Cutter bars (Hedgecutters)
Drive & clutch cable surfaces
Nylon Lines (Line Trimmers)
Carburettor cleaning
Bearings
Bushes
Electric cable
Grass collectors

3. Not covered by this warranty

(a) The warranty policy does not cover any depreciation or damages caused by ordinary wear, rusting or corrosion, lack of correct maintenance or operation, misuse, abuse, lack of transportation or accident.

(b) The warranty policy does not cover any costs necessary for the standard periodic maintenance services instructed by the operators manual, or service parts replacement which would include oil, filters, tyres, belts, brake linings, fuses, blades, seals and other service parts unless it can be proven that the item has evidence of faulty manufacture.

(c) The warranty policy will not cover failure or damage caused as a result of parts or accessories being modified without the written approval of GJ Handy & Co Ltd.

(d) The warranty policy will not cover the unit if non-genuine parts have been fitted and as a result damage has occurred to the unit.

(e) The warranty policy is non-transferable and is only applicable to the original purchaser.

4. Disclaimer

(a) This warranty is only a remedy for defect of products. GJ Handy & Co Ltd will never warranty in terms of the merchantability or the fitness for a particular purpose.

(b) No person is authorised to make any warranties, representations or promises, expressed or implied, on behalf of GJ Handy & Co Ltd, or to modify the terms conditions or limitation of this warranty policy in any way.



Instruction Manual

(c) Neither GJ Handy & Co Ltd nor any company affiliated with GJ Handy & Co Ltd shall be liable in any event or manner whatsoever for incidental or consequential damages or injuries, including, but not limited to, loss of crops, loss of profit, out of pocket expenses or profits, rental of substitute equipment or other commercial losses.

5. General

(a) Most warrantable failures show up within the first few weeks of use. These failures are usually straightforward and warranty assessment is relatively easy.

(b) Failures relating to cutter decks and belts need careful investigation, as the cause may not always be straightforward. Look for damage to blades and pulleys especially when the cutter belt or blade boss have snapped or cracked as this could be due to impact damage.

(c) Customers should always refer to the operator/instruction manual when any disputed problem arises, you will find most areas covered within the manual.

Protecting your machine

Maintenance

Regular maintenance of your Webb machine is essential to ensure it operates, safely, efficiently and therefore reducing the environmental impact.

It is the owner's responsibility to ensure that their Webb machine is maintained at specific intervals. Any approved Webb service dealer can undertake a service, which are specialised in our products and will be aware of your particular machine and any technical updates which will save valuable time & money.

If you are using your machine in dry, dusty or high temperatures, you will need to service the machine more regularly.

Fuel (if applicable)

Due to ongoing efforts by fuel companies to reduce emissions, unleaded petrol will oxidize & deteriorate in storage overtime, leaving residue from detergent components.

Fuel deterioration problems may occur when petrol is stored for over 30 days. If you are planning to store fuel for over 30 days, we recommend you add Handy Parts Sure-Start fuel stabilizer to fresh fuel after purchasing. Sure-Start cannot reconstitute stale fuel.

Storage

When storing your machine for an extended period, we do recommend that you follow the instructions of engine instruction manual.

Always store the fuel in a clean, approved and sealed container. If the container is steel, ensure it is not corroded. If the container is not filled to its recommended capacity, air can accelerate fuel deterioration.

Always store fuel away from direct sunlight, in a dark, cool environment.

Your servicing Webb approved dealer will stamp & date the below relevant sections, when the correct service actions have been completed.
PLEASE ENSURE THE SERVICE BOOK IS AVAILABLE FOR THE DEALER, DURING SERVICE WORK.

1st Service

This must be stamped by an approved service dealer to qualify for a free second year warranty.
(Excluding the Webb Electric Handheld machines)

12 Months

Date

24 Months

36 Months

Date

Date



Instruction Manual

48 Months

Date

60 Months

Date

72 Months

Date

84 Months

Date

96 Months

Date

108 Months

Date

120 Months

Date

132 Months

Date

Product Information (* Compulsory)

Personal Information (* Compulsory)

You may give Webb Lawnmowers notice in writing at any time that you no longer wish to receive direct marketing communications

Webb Lawnmowers
Murdock Road
Dorcan
Swindon
Wiltshire
SN3 5HY